



Material description

Acoustic fence modules made of hot-dipped galvanized steel, ROCKWOOL stone wool (core and acoustic material) and green PE fabric.

Noise damping features

Features	Value
Sound insulation	22dB according to EN 1793-2 (B2)
Sound absorption	8dB according to EN 1793-1 (A3)

Product dimensions*

Length [cm]	Height [cm]	Width [cm]	Weight per element [kg]	Element per pallet
100	100	11	30,0	20
200	100	11	60,0	10
200	90	11	53,5	10
200	50	11	30,0	20
300	60	11	53,5	20 or 10
300	40	11	36,0	20

* Selected other sizes are available upon request.

Storage condition advice

Preferably stored inside. If stored outside:

- Stack max. 2 pallets on each other.
- Remove plastic foil to prevent trapped humidity.
- Protect against high quantities of UV to prevent “natural ageing” of exposed products only, especially when stored for longer periods of time.
- Preferably cover the top of the product package to prevent unnecessary exposure to elements by roof or single cover.

Decorative surface

Value
Green PE fabric (Polythene)

Steel frame and grid

Features	Value
Galvanisation	Hot dip galvanized steel according EN ISO 1461-1999
Powder coatings	Green RAL 6005, Anthracite RAL 7016, Black RAL 9005, White RAL 9010

Mechanical strength

Features	Value
Wind load resistance	Tested to maximum load 2.4 kN/m ² according to EN1794-1

Durability

Noistop Steel uses a combination of robust galvanized steel, and highly durable ROCKWOOL stone wool with a typical service lifetime of over 30 years. The steel frame is hot-dip galvanized steel according EN ISO 1461-1999 which typically provides steel protection well beyond 50 years. Please note that durability of the product strongly depends on the specific environmental characteristics in which the product is applied.

Contact details



Address	ROCKWOOL B.V. Delfstoffenweg 2 6045JH, Roermond The Netherlands
Contact	Barbara Anstötz
Phone	+45 25265744
E-mail	info@lapinus.com
Website	www.lapinus.com/applications/fences/

The greatest possible care has been taken in designing and putting together this communication. However, Lapinus cannot issue any warranty relating to the completeness and accuracy of the information gathered, processing of information, results of the calculations, advice, example constructions and other results. All calculations, advice, example constructions and other results are approximations or typical values and will not bind Lapinus. Please also note that the performance of the product in a construction or system strongly depends on the parameters of such a construction or system, such as but not limited to local soil conditions, the quality of the installation and other components. All of these parameters fall outside the scope of influence of Lapinus. As a consequence, no warranty can be provided by Lapinus as regards the performance of the product. All rights are reserved. No part of this communication may be reproduced or published by means of print, photo print, microfilm or any other means without Lapinus' prior written permission. The contents of this communication are subject to amendment without notification. Although every care was taken during the preparation of this communication, Lapinus cannot accept liability whatsoever for errors in this communication, nor for their consequences.

This disclaimer is provided by ROCKWOOL BV, trading as Lapinus. We are registered in the Netherlands under company number 13014428. Please contact Lapinus Customer Service for additional information or questions (+31 475 35 35 55).